



ORDER INFORMATION

BT05 - P - HXX - XX
 Series Base Height No. of pos
 P : Plug
 S : Socket

	A	B	C	D
10P	5.20	2.00	2.90	3.90
12P	5.70	2.50	3.40	4.40
14P	6.20	3.00	3.90	4.90
16P	6.70	3.50	4.40	5.40
18P	7.20	4.00	4.90	5.90
20P	7.70	4.50	5.40	6.40
22P	8.20	5.00	5.90	6.90
24P	8.70	5.50	6.40	7.40
26P	9.20	6.00	6.90	7.90
28P	9.70	6.50	7.40	8.40
30P	10.20	7.00	7.90	8.90
32P	10.70	7.50	8.40	9.40
34P	11.20	8.00	8.90	9.90

	A	B	C	D
36P	11.70	8.50	9.40	10.40
38P	12.20	9.00	9.90	10.90
40P	12.70	9.50	10.40	11.40
42P	13.20	10.00	10.90	11.90
44P	13.70	10.50	11.40	12.40
46P	14.20	11.00	11.90	12.90
48P	14.70	11.50	12.40	13.40
50P	15.20	12.00	12.90	13.90
60P	17.70	14.50	15.50	16.40
80P	22.70	20.40	20.50	21.40
100P	27.70	25.40	25.50	26.40

HIGH	PLUG	SOCKET
3.0	0.8	2.2
3.5	1.3	2.2
4.0	1.0	3.0
4.5	1.0	3.5
5.0	2.0	3.0
5.5	2.0	3.5
6.0	2.0	4.0
6.5	2.0	4.5

DRAWG NO		PLUG		PA 9T	C5210R-1/2H : t0.2		TREATMENT	REFERENCE
PART NAME		MATERIAL	QUANTITY	SPECIFICATION				
THRO	ANGLE	UNIT	SCALE	TOLERANCE		WK NAME	0.5mm PLUG	
PROJ		mm	n/s					
APPR	CHECK	DESIGN	DRAW					
MARK	DATE	REVISION	SIGN					
						PART NAME	0.5mm BOARD TO BOARD	
						DRAWG NO.	BT05-P	